

ISO Max V Scanner



- Reads all US microchip frequencies
- Reads from up to 10" away
- Reads through non-conductive materials like plastic carriers
- Provides audio confirmation of successful reading
- Stores up to 2,000 microchip numbers with date/time stamp
- Powered by rechargeable lithium-ion battery

Dimensions

- 13" x 6.3" x 1.57" (33 x 16 x 4 cm)

Weight

- 15.87 ounces (450 grams)

Operating Temperature

- 23 °F to 113 °F (-5 °C to 45 °C)
- 95% RH, non-condensing

Operating Temperature

- (while battery is charging)
- 32 °F to 104 °F (0 °C to 40 °C)
- 95% RH, non-condensing

Storage Temperature

- -40 °F to 158 °F (-40 °C to 70 °C)
- 95% RH, non-condensing

Power Supply

- Rechargeable lithium-ion battery
- Two hour charge time

Frequency

- Reads all US microchip frequencies: 125 kHz, 128 kHz and 134.2 kHz

Memory

- Stores up to 2,000 microchip numbers with date/time stamp

Read Distance

- FDX-B up to 9.85" or 25 cm
- FDX-A/FECAVA up to 5.90" or 15 cm
- Avid encrypted up to 5.90" or 15 cm
- Trovan 10 digit up to 3.50" or 9 cm

Housing

- White ABS Plastic

Certifications

- CE, FCC

Accreditations

- ISO 11784 & 11785

For more information about Found Animals Registry products, please visit

www.found.org/products

Phone: 844-523-3872 Fax: 213-402-7799

PO Box 66370, Los Angeles, CA 90066